Brief Specification.

1.6mm panels: 2 Corri Profile Base Plates: Std Slotted Top Plates: Std top lift Jacklegs: Brackets only Lifting Points: N/a Fork Lift Tunnels: N/a

Staircase fixings: Fixing Bolts

Link Frame: N/a

Wall Panel Height; 2485mm

Underdrawn; Yes

Insulated walls 50mm TP10 Floor 80mm TP10

Roof 70mm Fiberglass + 40mm TP10

O/A 2440

External Finishes Mid-Sheen

Main Body: TBC Fascia & gutters: TBC

Jacklegs: TBC Plinth: TBC Door: TBC Shutters: TBC

Internal finish

O/A 6100 3050 J/Lea Bracket Ctrs

Jacklegs Not Fitted

Unit lined in 15mm plasterboard c/w 'H' section joints to wall and ceiling to achieve 1 hour fire resistance in to out

45A Cooker

Point

Walls 15mm pl/bd Vinyl Faced; Cream Ceiling 15mm pl/bd Vinyl Faced; White Floor Polyflor XL 2mm: Mushroom 9110 Plastic door & window lining; Cream

Internal Door Architrave; Brown

Skirting: Brown (2 part) Skirting to WC; Black PVC Top lath; Brown (2 part)

'H' Sections; To Suit Board Finish Internal Corners; Brown (2 part)

Windows - UPVC

White finish double glazed **Prod No:** T&T 914h x 914h @ 980mm affl

White finish double glazed **I.D Plate**:

HL3 600w x 400h

HL Frame @ 1721mm affl

Timber Framing: 45mm

1500 Fluorescent LED Light

Fleet No: Stickers:

Kev: Distribution Board

2D Bulkhead


Wall Light Switch Pull Cord Light Switch

13A Double Socket

Oil Filled Radiator

10L Undersink Water Heater 7Kw Shower Unit Low Voltage Extractor Fan

45A Cooker Point



20' x 8' Accomodation Unit



2X5DL

Client:

Project:

Title:

Plan Layout

Description: By: Date: Rev:

Date: Drawn: Scale:

1:50 @ A4 13.05.15 WH

Dwg No: Rev:

05.3902.01